

APU419 device for XPG

The APU419 is a chosen hardware of the XPG (Secure StreamX Protocol Gateway) product family. The APU419 is a fanless computer running quad core CPU, robust Intel NICs and low total solution cost. With its high-performance components, the APU419 meets all requirements of communication applications, data processing and protocol conversion and is extremely flexible in operation and integration.



Specifications

Computer

CPU	AMD GX-412TC quad core
DRAM	4 GB
Storage	m-SATA 16 GB
Operating System	ISOS (Industrial Secure Operating System)
Communication Software	StreamX
Redundancy	Supported

Interfaces

Serial	1x RS-232
LAN	4x or 6x LAN ports GbE
Cellular	Optional
LED indicators	10x

Operating conditions

Working temperature	-10°C to +60°C
---------------------	----------------

Physical

Supply voltage	230 VAX or 24-48 VDC
Redundant supply voltage	Optional
Installation	Rackmount 19" 1U
Dimensions	Rack 19": W*D*H in mm 482.6 * 266 * 43.8

Product Overview

Models

APU419L4P1230	1x 230 VAC	4x LAN ports GbE
APU419L4P136	1x 24-48 VDC	4x LAN ports GbE

Options

APU-ACC-2LAN	2 additional LAN
APU-ACC-PS230	2 nd supply voltage 230 VAC
APU-ACC-PS24	2 nd supply voltage 24-48 VDC
APU-ACC-MDM4G	Mobile Radio Module 4G

Request for offer

We will be pleased to consult you on your project or propose a non-binding offer. Please send this form with your contact data to info@elvexys.com to learn more about APU419.

Positions

Quantity

APU419L4P1230	1x 230 VAC
APU419L4P136	1x 24-48 VDC

Options

APU-ACC-2LAN	2 additional LAN
APU-ACCPS230	2 nd Supply voltage 230 VAC
APU-ACC-PS24	2 nd Supply voltage 24-48 VDC
APU-ACC-MDM4G	Mobile Radio Module 4G

[General terms and conditions](#)